





Toroidal transformer type 7N1934




primaries in parallel
for 115V input





secondaries in parallel
for 115V output



primaries in series
for 230V input



secondaries in series
for 230V output



primaries: 2x 115V
secondaries: 2x115V 1.3A
total power rating:300VA
regulation: 7%

Diameter 123mm
Height 59mm
Weight 3.1kg
Height and weight are measured without mounting materials
All leads are solid and approx 200mm long

Supplied mounting materials:
1 metal washer Ø9cm
2 neoprene washers Ø9cm
1 bolt M5x70 with nut

Approvals:
KEMA KEUR & ENEC to EN61558, KEMA certificate 2159403.02
UL/CSA to UL506 & CSA22.2, UL file number E320377
Built and tested according to EN60601-1:2006+A11:2011 (3rd ed.)
Protection level: effectively 2 MOPP
CE marking.

Built-in selfresetting thermal cutout to be switched in series with all primaries.

Time lag fuses to be used.
for 230V primary: 1.6A, 5x20mm, IEC127, high I²t value
for 115V primary: 3.15A, 5x20mm, IEC127, high I²t value
in series with 2 NTC-resistors type NTC2.5

Secondary: none



Industrieweg 14
NL-7161BX NEEDE
The Netherlands

P O - B o x 27
NL-7160AA NEEDE
The Netherlands
Tel.+31 (0)545 283456
Fax+31 (0)545 283457

info@amplimo.nl
http://www.amplimo.nl

HB

Oct 2020

7N1934

toroidal power transformer
for medical purposes

© Copyright Amplimo BV