






### Toroidal transformer type 58013



serial operation to double the secondary voltage



parallel operation to double the secondary current



Power rating 160VA  
Primary voltage 230VAC - 50/60Hz  
Secondary voltages 2x 15V - 5.33A  
Regulation 7%

Diameter 110mm  
Height 43mm  
Weight 1.9kg  
Height and weight are measured without mounting materials  
All leads are solid and approx 200mm long

Supplied mounting materials:  
1 metal washer Ø90mm  
2 neoprene washers Ø90mm  
1 bolt M5x50mm with nut

KEMA KEUR, ENEC approvals, certificate 2159403.01  
UL/CSA approvals, UL filenumber E320377.  
CE, RoHS-compliant

Time lag fuses to be used.  
Primary: 0.8A, 5x20mm, IEC127, high I<sup>2</sup>t value  
Secondary: none

230V 50Hz / 60Hz 160VA



Industrieweg 14  
NL-7161BX NEEDE  
The Netherlands  
  
P O - B o x 2 7  
NL-7160AA NEEDE  
The Netherlands  
Tel.+31 (0)545 28 3456  
  
info@amplimo.nl  
https://www.amplimo.nl

HB	Oct 2010
HB	Feb 2023
©	Copyright Amplimo BV

**58013**  
**toroidal transformer**  
**160VA**